

PRESSURE SWITCH



INTL-Y001
3/8-24 UNF Male
HP:(A)26.5kg/cm² Off
(B) 31.4kg/cm² Off
LP:2.0KG/Cm² Off
R-12 R-134a



INTL-Y002
Standard Type
OE#124-820-59-10
3/8-24UNF Male Off:2.1kg/cm²
R12



INTL-Y003
M11-P1.0 Male
HP:31.4kg/cm² Off
LP:2.0KG/Cm² Off
R-12 R-134A



INTL-Y004
Ford/Mazda
3/8-24 unf Male
HP:(A) 27KG/Cm² Off
(B) 32kg/cm² Off
(C) 30kg/cm² Off
LP:2.0KG/Cm² Off
R-12 R-134A



INTL-Y005
Mitsubishi 3/8-24 UNF Male
HP:(A) 27KG/cm² Off
(B) 32kg/cm² Off
© 30kg/cm² Off
LP:2.0KG/Cm² Off
R-12 R-134A



INTL-Y006
Toyota
3/8-24 UNF Male
HP:3.14Mpa Off
MP:1.52Mpa On
LP:0.196 Mpa Off
HFC-R134A



INTL-Y007
Honda Crv



INTL-Y008
Ford LINCOLN MAZDA MERCURY YH552 YH-552
F3AH-19E561-AA



INTL-Y009
NISSAN
3/8-24 unf Male
HP: 27KG/cm² Off
LP:2.0KG/cm² Off
R-134A 2Pin



INTL-Y010
Hyundai
3/8-24 UNF Male
HP:3.14Mpa Off
MP:1.77Mpa On
LP:0.196 Mpa Off
HFC-R134A 4Pin



INTL-Y011
Opel 4Pin
OE# 507773900
7/16-20 UNF Female
HP:28 bar Off
MP:15.2 bar On
LP:3.5 bar Off



INTL-Y012
GENERAL MOTORS/VOLVO
OE:15-2960
M12-P1.5 FEMALE
ON:3.1kg/cm² on
OFF:1.7kg/cm² off
ADJUSTABLE ± 0.5kg/cm²
R-134a



INTL-Y030
TOYOTA CAMRY Prius Sienna
499000-7880



INTL-Y032
VW GOLF - 2001> 2005 FOX - 2003>
1J0959126 8Z0959126



INTL-Y033
GM BUICK CHEVROLET CADILLAC RENAULT FIAT
22678731 1550147 22634172



INTL-Y034
BMW E82 E88 E21 E46 E90
64539181464 64536909257